



Remote Cargo Hook Test Form

4.5NR

Work Order _____

Customer _____

Serial Number _____

Date _____

# of Releases	Load (Lbs.)	Release Method	Remarks	Result	Pass/Fail
1	11,250	Static Hold	Hold for two Minutes and reduce load to zero	N/A	
10	2,250	Electircal, 25 volts	No "hang ups" permitted	N/A	
2	4,500	Electircal, 22 volts	Current shall not exceed 4.5A	A	
2	3,500	Electircal, 22 volts	Current shall not exceed 4.5A	A	
2	2,500	Electircal, 22 volts	Current shall not exceed 4.5A	A	
2	1,500	Electircal, 22 volts	Current shall not exceed 4.5A	A	
2	500	Electircal, 22 volts	Current shall not exceed 4.5A	A	
1	4,500	Electircal, 20 volts	Current shall not exceed 4.1A	A	
1	4,500	Electircal, 28 volts	Current shall not exceed 5.7A	A	
1	4,500	Manual		N/A	
1	N/A	Solenoid Ohms	Shall not exceed 4.9-5.6 Ohms	Ω	
1	N/A	Electircal Continuity	Across both wires	N/A	

Test Conducted By: _____
Technician

Signature: _____
QC 5 Small FAB / QA